

PRODUCT CODE: NLA0615SA	COMMERCIAL NAME: IDROTAN BIANCO 615 A
DESCRIPTION	Water-based fill for exterior

PROPERTIES	
Recommended for / Main area of application	Water-based pigmented filler for exterior ready for use. Suggested for shutters and manufactured objects. Suitable for broad-leaved woods. This product modifies the physical characteristics of the wood by removing the porosity and by preventing the flaking. Thanks to its properties, it makes the manufactured object resistant to weather exposure.
Application Method	By dipping, by flow coating
Shelf life	12 Months

APPLICATION PROPERTIES		PHISICAL PROPERTIES	
Quantity	-	Viscosity	50 " +/-6" DIN 2
Vertical Stability	-	Solid Content	20.8 +/-1 %
Cathalysis	-	Specific Weight	1.180 +/-0,020 Kg/Lt
Dilution	-	Glossy	-
Pot Life	Illimited	Ph	-

GENERAL INFORMATION			
Drying at 20°C		Oven Drying	
Dust Free	15'	Time for Flash Off	-
Touch Free	30'		
Sanding	2 h	Time for drying	-
Overcoating	2 - 4 h		
Stackable	4 h	Time for cooling	-

RECOMMENDED APPLICATION PROCESS
Apply by dipping NLA0615SA- IDROTAN BIANCO 615 A. After 2 - 4 hours apply a coat of a water-based transparent sealer, suggested N080SA - IDROFOND 610 TX EST. After 4 - 6 hours sand with sand paper 220 - 400 and apply a coat of a water-based transparent to pcoat, suggested serie N150...SA - IDROMAT 520 TX EST VARI GLOSS.

ALTERNATIVE HARDENERS	PERFORMANCES
-	-
-	-
-	-

ALTERNATIVE THINNER
-

NOTES	User is responsible to make the application of the product in a place with an adequate air-recycle and on respecting of all hygienic and safety regulations.
--------------	--



TECHNICAL DATA SHEET

Release: 0

Date: 24/11/2017

STORAGE	Don't keep product in a place with temperature < 5°C and > 35°C. The drying of waterbased products must take place in suitable and well ventilated places (temperature > 15°C and relative humidity < 85%).
---------	---